

80 WATT | 150 WATT | 230 WATT

FLOODLIGHTS LINEAIR



FLOODLIGHTS LINEAIR WAREHOUSE

De Floodlight Lineair is speciaal voor warehouses, magazijnen en opslag met stellingen. Door de juiste graden van de lichtstraal met een uitstekende lumen opbrengst zijn de armaturen uitermate geschikt om brede gangpaden en stellingen uit te lichten.

Er wordt gebruik gemaakt van Osram of LumiLEDs. Door het gebruik van hoogwaardig materiaal wordt de warmteontwikkeling snel en juist gekoeld. Hierdoor is er een lange levensduur en zal de lichtopbrengst niet snel afnemen. L85/B15 bij 50.000 branduren.

TOEPASSINGEN

Industrieel | Werkplaats | Magazijn | Fabriek | Warehouse


STRALINGSHOEKEN



VERMOGEN



KLEURTEMPERATUUR



QueLED Floodlights Linear

SPECIFICATIES

LED	Product Code	QL261520 - QL261523
	LED Chip supplier	Osram
	LED Type LED	Osram Lumileds
	LED Quantity LED	80 LEDs / 160 LEDs / 240 LEDs
	Colour Temp. (K)	4000K/5000K
	Tolerance	±5%K
	SDCM	<3
	CRI (Ra)	>85
Power supply	Driver	Isolated driver
	Driver Brand	Meanwell
	Input Voltage	AC100-240V
	Frequency Range	50Hz-60Hz
	Wattage	80W / 150W / 230W
	Power Factor	0,96
	Ambient Temp	(-10°C ~ +40°C)
	Dimmable?	1-10V / DALI optional
Design Parameters	Size (mm)	Φ400mmx188mm
	Finish color	Black
	Beam Angle	45°/60°/70°/90°/120°/Symmetrical/Round beam
	Lumen Output	10400lm / 19500lm / 29900lm
	Luminous Efficiency	130lm/w
	Tolerance	±5%lm
	Material	Die-cast Aluminium / Tempered glass
	Light Design	LED and novellight
	IP rate	IP65
	IK rate	IK09
	Certificate	TUV/GS/CB/UL/ETL
	Lifetime	50,000 hrs
	Junction Temperature	≤ 80 °C
	Working temperature	-30°C ~ +55°C
Storage temperature	-25°C ~ +65°C	
Packing information	Installation type	Suspended Mounting
	Packaging Lamp body	420mm x 250mm x 170mm 690mm x 250mm x 170mm 1010 mm x 250 mm X 170 mm