

150 WATT | 200 WATT

LED HIGH BAY DESIGN



LED High Bay Design armaturen

HighBay High End design series hebben een uitstekende thermisch managementsysteem waardoor de Osram LED's of Lumileds continue worden gekoeld. Hierdoor een langere levensduur is gewaarborgd en de presentatie aanzienlijk verhoogt. Door gebruik te maken van een High End LED driver van Meanwell is de combinatie compleet.

- Volledige garantie van 5 jaar op het product (L85/B10).
- Door de rotable beugel van 180° kan deze zowel aan een oppervlakte als aan de muur gemonteerd worden.
- Transparantie PC-hoes en de 60 ° of 90 ° graden reflector kap zijn uitwisselbaar.

TOEPASSINGEN

Industrieel | Werkplaats | Magazijn | Fabriek | Warehouse

STRALINGSHOEKEN



45°



60°



70°



90°



120°



Symetrisch



Round beam

VERMOGEN



150W



200W


KLEURTEMPERATUUR



4000
KELVIN



5000
KELVIN



QueLED High bay Design

SPECIFICATIES

LED	Product Code	QL261520 - QL261523
	LED Chip supplier	Osram
	LED Type LED	Osram Lumileds
	LED Quantity LED	224 LEDs / 252 LEDs
	Colour Temp. (K)	4000K/5000K
	Tolerance	±5%K
	SDCM	<3
	CRI (Ra)	>85
Power supply	Driver	Isolated driver
	Driver Brand	Meanwell
	Input Voltage	AC100-240V
	Frequency Range	50Hz-60Hz
	Wattage	150W / 200W
	Power Factor	0,96
	Ambient Temp	(-10°C ~ +40°C)
	Dimmable?	1-10V / DALI optional
Design Parameters	Size (mm)	Φ400mmx188mm
	Finish color	Black
	Beam Angle	45°/60°/70°/90°/120°/Symmetrical/Round beam
	Lumen Output	19500lm / 26000lm
	Luminous Efficiency	130lm/w
	Tolerance	±5%lm
	Material	Die-cast Aluminium / Tempered glass
	Light Design	LED and novellight
	IP rate	IP65
	IK rate	IK09
	Certificate	TUV/GS/CB/UL/ETL
	Lifetime	50,000 hrs
	Junction Temperature	≤ 80 °C
	Working temperature	-30°C ~ +55°C
	Storage temperature	-25°C ~ +65°C
Packing information	Installation type	Suspended Mounting
	Packaging Lamp body	440mmx200mm