

IP69K

SMART TRI-PROOF LIGHT



- IP69K is waterdicht, zeer sterk en gemakkelijk te reinigen
- Eenvoudig te installeren en kunnen in serie geschakeld worden
- Anti UV, vervaagt niet makkelijk, V0 brandveilig
- RoHS, CE, TUV, SAO certificering
- Corrosie bestendig

Zeer goed toepasbaar voor de levensmiddel industrie, stallen, magazijnen, supermarkten etc. Door de weersbestendigheid en brandveiligheid uitermate geschikt voor buiten en vochtige ruimtes.

De armaturen zijn verkrijgbaar met de volgende opties:

- Dimbaar 1-10V / Triac
- Sensor
- Emergency
- Mogelijkheid met CCT van 4000K tot 6000K regelbaar
- Het vermogen kan regelbaar worden ingesteld

TOEPASSINGEN

Industrieel | Werkplaats | Magazijn | Fabriek | Warehouse

STRALINGSHOEKEN



VERMOGEN



KLEURTEMPERATUUR





QueLED Smart Tri-proof light

SPECIFICATIES

LED	Product Code	QL251501 - QL251516
	LED Chip supplier	Epistar
	LED Type LED	SMD2835
	LED Quantity LED	
	Colour Temp. (K)	4000K/4700K
	Tolerance	±5%K
	SDCM	<4
	CRI (Ra)	>85
Power supply	Driver	
	Driver Brand	
	Input Voltage	AC100-277V
	Frequency Range	50Hz-60Hz
	Wattage	50W / 70W
	Power Factor	0,96
	Ambient Temp	(-10°C ~ +40°C)
	Dimmable?	Dimmable (0-10V, DALI), Emergency Battery, Microwave Sensor
Design Parameters	Size (mm)	Ø 48 mm x 1200 mm Ø 48 mm x 1500 mm
	Finish color	White
	Beam Angle	75° / 120°
	Lumen Output	7500 lm / 10500 lm
	Luminous Efficiency	130 - 150 lm/w
	Tolerance	±5%lm
	Material	Resist in 4000V lightning stroke, V0 fireproof. Anti-UV and not easy to fade
	Light Design	
	IP rate	IP69
	IK rate	IK10
	Certificate	TUV/GS/CB/UL/CE/SAO/RoHS
	Lifetime	50,000 hrs
	Junction Temperature	≤ 80 °C
	Working temperature	-30°C ~ +55°C
	Storage temperature	-25°C ~ +65°C
Packing information	Installation type	Suspended Mounting, connect in series by terminal
	Packaging Lamp body	1350mm x 450mm x 210mm / 1650mm x 450mm x 210mm