

24 WATT | 32 WATT | 45 WATT

# LED TRI-PROOF R-SERIES



## LED Tri-proof Light - R series

- Hoge beschermingsklasse IP 67/68
- Toepassing voor het wassen met warm water IP69K
- Mechanische sterkte: Impact Weerstand
- Rang IK08-10 in geval van opzettelijke sabotage
- Glazen onderdelen uitgesloten UV bestendig, anti-UV
- Ammoniak weerstand.
- Weerstand tegen corrosie
- Hoge Color rendering index :CRI=80,CRI 90 is optioneel

### TOEPASSINGEN

Industrieel | Werkplaats | Magazijn | Fabriek | Warehouse

#### STRALINGSHOEKEN



#### VERMOGEN



#### KLEURTEMPERATUUR





# QueLED Tri-proof - O series

## SPECIFICATIES

<b>LED</b>	Product Code	QL901101 - QL901106
	LED Chip supplier	Lumileds
	LED Type LED	Lumileds
	LED Quantity LED	
	Colour Temp. (K)	4000K/5000K
	Tolerance	±5%K
	SDCM	<3
	CRI (Ra)	>85
<b>Power supply</b>	Driver	
	Driver Brand	
	Input Voltage	AC100-240V
	Frequency Range	50Hz-60Hz
	Wattage	24W / 32W / 45W
	Power Factor	0,96
	Ambient Temp	(-10°C ~ +40°C)
	Dimmable?	1-10V / DALI optional / Zigbee optional
<b>Design Parameters</b>	Size (mm)	48 mm x 1200 mm   48 mm x 1200 mm
	Finish color	White
	Beam Angle	75° / 120°
	Lumen Output	3120lm / 4160lm / 5850lm
	Luminous Efficiency	130 lm/w
	Tolerance	±5%lm
	Material	Applicable for washing by hot water IP69K
	Light Design	Glass parts excluded UV resistance, anti-UV
	IP rate	IP67 / 68
	IK rate	IK10
	Certificate	TUV/GS/CB/UL/ETL/ENEC
	Lifetime	50,000 hrs
	Junction Temperature	≤ 80 °C
	Working temperature	-30°C ~ +55°C
	Storage temperature	-25°C ~ +65°C
<b>Packing information</b>	Installation type	Suspended Mounting
	Packaging Lamp body	1300mm x 75mm x 75mm / 1600mm x 75mm x 75mm